

MODEL SA11-D6 / SA11-D10 SEALERS

FOR REGULAR AND HIGH-TENSILE STEEL STRAPPING



- Hardened tool steel parts for
- Double up-notch seal for high joint efficiency
- Compatible with feed wheel
- Easy replacement of wearing
- Ideal for regular shaped
- Available for 3/4" and 11/4"
- Samuel quality built in to



MODEL SA11-D6 / SA11-D10 Sealers

FOR REGULAR AND HIGH-TENSILE STEEL STRAPPING

Description


Samuel SA11 sealers have been designed for a broad range of common strapping applications. These sturdy sealers are built with hardened tool steel, to provide you with a lifetime of reliable use under demanding conditions. The SA11 is available in two models which can handle standard and high tensile strapping in gauges of 3¼" and 11¼". Used in combination with a standard feedwheel type tensioner, the SA Series sealer is designed to crimp an open flange seal in a double up-notch configuration.




Represented By:	
,	
CA11 DC/D10 00/11 040F0	

Parts

	Item	Qty	SA11-D6 Part #	SA11-D10 Part #	Description
	1	2	C19343F	C19337F	Side plate
	2	2	D42127A	D43047F	Top link
	3	2	D41607F	D41607F	Roller
	4	4	D42123F	-	Punch
	4a	2	-	D46427F	Punch, outside
	4b	3	-	D41601F	Punch, center
	5	2	D42128F	D46437F	Spacer
	6	4	C20166F	C20479F	Jaw
	7	2	D43797F	D42118F	Pivot pin
	8	1	D42126F	D46452F	Rear link
	9	1	D42125F	D43048F	Front link
	10	1	B12361A	B12509A	Upper handle assembly
	11	1	B12624A	B12623A	Lower handle assembly
	12	3	D31231F	-	Screw, .312-24 x 1.75 Hex Hd
	12b	3	-	D67411F	Screw, .312-24 x 2.25 Hex Hd
	14	1	D43796F	D73865F	Stud
	15	2	D42072F	D42072F	Nut, .250-28 elastic stop
	16	2	HT321A (ISP)	HT321 (ISP)	Jaw pivot pin
	17	2	CB836 (ISP)	CB836 (ISP)	Retaining E-ring
	18	1	D43798F	D42117F	Handle pivot bolt
	19	1	D43801F	D43801F	Nut, .375-24 thin elastic stop
	20	3	HT324 (ISP)	D43123F	Nut, .312-24 elastic stop
	21	2	HT305A (ISP)	HT305A (ISP)	Handle grip





SA11-D6/D10-02/11-94950