

Battery powered plastic strapping tool for demanding applications

**Characteristics**

Strapping qualities:	Polyester (PET) and Polypropylene (PP) plain and embossed
Strapping dimensions:	width 16.0 – 19.0 mm / 5/8 – 3/4" thickness 0.65 – 1.35 mm / .026 – .053"
Weight incl. battery:	4.2 kg / 9.3 lbs
Tool size with battery:	L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6"
Type of seal:	Friction weld sealing
Average seal strength:	approx. 75% (dependent on strap quality)
Tension force:	500 – 4000 N / 112 – 900 lbs (adjustable)
Tension speed:	49 – 79 mm/s / 1.9 – 3.1 inch/s
Power supply:	Battery Li-Ion 18VDC / 4.0 Ah
Suspension bracket:	optional

Advantages

- High tension force up to 4000N / 900 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single button) version available for efficient operation
- Brushless motor for less maintenance and improved life time
- Improved plates and guides – less effort to remove the tool from the strap
- No tension rocker – easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating
- Cycle counter included (special reader required)
- Battery well protected
- Battery charge indicator included
- Simple one-handed operation
- Tool is fully covered for finger protection
- Optional motor cooling fan available to reduce overheating risk

Chart of types model P329

Item no.	Model	Strap widths		Strap thicknesses		Max. tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.2522	P329/16/0.65-1.05	16	5/8	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2532	P329/19/0.65-1.05	19	3/4	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2533	P329/19/1.06-1.35	19	3/4	1.06-1.35	.042-.053	4000	900	49-79	1.9-3.1
43.2722	P329/16/0.65-1.05/A	16	5/8	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2732	P329/19/0.65-1.05/A	19	3/4	0.65-1.05	.026-.041	4000	900	49-79	1.9-3.1
43.2733	P329/19/1.06-1.35/A	19	3/4	1.06-1.35	.042-.053	4000	900	49-79	1.9-3.1

A = Automatic model

Battery chargers for model P329

Item no.	Model	Voltage / frequency	Countries
N5.4443	Li-Ion battery charger	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, BY, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, (BRN), (BRU), (CY), (EAK), (EAT), (GB), (IRL), (M), (MAL), (OM), (SGP), (Y), (Z), (ZA), (ZW)
N5.4447	Li-Ion battery charger	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4445	Li-Ion battery charger	220-240 V / 50-60 Hz	AUS, NZ

(..) = Adapter N52.2102 required

Battery for model P329

Item no.	Battery	Voltage	Capacity	Charging time
N5.4349	Accu Li-Ion	18VDC	4.0 Ah	approx. 80 min.

Accessories

P32.0223	Suspension bracket
P32.0226	Wearing plate (metal) for rough and hard surfaces
P32.0227	Protection plate (plastic) to protect complete bottom side
P32.0228	Motor cooling fan
N7.5154	Cycle count reader



SiTco
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية
SEASON INTERNATIONAL TRADING & INDUSTRIES CO.

P.O. Box 886, Manama - Kingdom of Bahrain, Tel: +973 17704647, Fax: +973 17704648
E-mail: info@seasoninternational.net, web: www.seasoninternational.net